# New Fire Extinguisher Requirements

## For Fishing Vessels Under 65 Feet In Length

Less Than 26 Feet In Length	One UL Rated 5-B	(Note 1)
26 Feet To Less Than 40 Feet In Length	Two UL Rated 5-Bs	(Note 2)
40 Feet To Less Than 65 Feet In Length	Three UL Rated 5-Bs	(Note 2)

- Note 1: Outboard boats less than 26 feet in length are not required to carry fire extinguishers if their construction will not permit the entrapment of explosive gases or vapors.
- Note 2: One UL Rated 20-B (or larger) may be substituted for two UL Rated 5-Bs.
- Note 3: Vessels with a CG Approved Fixed Fire Extinguishing System in their engine room may reduce their required number of portable fire extinguishers by one.

#### For Fishing Vessels 65 Feet Or More In Length

Constitution I	Min.	0.000
Space Aboard Vessel	Rating	Quantity and Location
Safety Areas, Communicating Corridors	2-A	1 in each main corridor not more than 150 ft. apart
		(May be located in stairways)
Pilothouse	20-B:C	2 in the vicinity of the exit
Service Spaces, Galleys	40-B:C	1 for each 2,500 sq.ft. or fraction thereof
		suitable for hazards involved.
Paint Lockers	40-B	1 outside space in the vicinity of the exit
Accessible Baggage & Storage Rooms	2-A	1 for each 2,500 sq.ft. or fraction thereof located in the
		vicinity of the exits, either inside or outside the spaces
Workshops & Similar Spaces	2-A	1 outside the space in the vicinity of the exit
Machinery Spaces; Internal Combustion Propelling Machinery	40-B:C	1 for each 1,000 brake horsepower or fraction
		thereof but not fewer than 2 or more than 6
Electric Propulsion Motors Or Generator Unit of Open Type	40-B:C	1 for each propulsion motor generator unit
Auxiliary Spaces	40-B:C	1 outside the space in the vicinity of the exit
Internal Combustion Machinery Spaces	40-B:C	1 outside the space in the vicinity of the exit
Electric Emergency Motors Or Generators	40-B:C	1 outside the space in the vicinity of the exit

### Fire Extinguisher Maintenance Requirements

## **Commercial Fishing Vessels**

#### Non-Rechargeable/Non-Refillable Extinguishers:

These are typically white aluminum canisters with plastic handles

Annual Maintenance may be performed by vessel owner, operator, person-in-charge or a designated member of the crew. Must be replaced when 12 years old. Date on tag must be within the last 12 months.



#### Rechargeable/Refillable Extinguishers:

These are typically red or yellow steel canisters with metal handles.

Annual Maintenance must be performed by a person certified/licensed by a state or local jurisdiction. Dry Chemical and Halogenated Agent extinguishers must undergo an internal visual examination and agent replacement every 6 years and a hydrostatic test every 12 years. Portable CO2 extinguishers must undergo a hydrostatic test every 5 years. Date on tag must be within the last 12 months.

